

StoSilent Prim



		StoPrim LP	StoPrim Isol.
	VdL-	:	
		DIN EN ISO 2811-2	1,0-1,1 /c ³
()		VIQP 033/VILS 001 (Sto	15-17 M-%
pH-		VIQP 011 (Sto .)	7-8
			StoColor Protect.
		PG II + III ():	
			PG IV – V:
30			StoSilent Prim. StoPrim LP.
		StoLevel In Z.	StoLevel In Fill.

StoSilent Prim



	<p>StoColor Protect.</p>
	<p>: + 5° C</p>
	<p>StoSilent Prim . 1 : 1. StoSilent Prim . OWApplan-Putzträger-</p>
	<p>(OWApplan- 0,2 / 2 0,4 / 2)</p>
	<p>StoSilent Prim ! (+ 20 °C/65% . -).</p>
	<p>... (.)</p>
GIS-CODE	M-GF01
	StoSilent Prim/DE/DE/017
	23.05.2006
	Sto.
Hauptsitz Sto AG	
Ehrenbachstraße 1	
D-79780 Stühlingen	
Tel. (0 77 44) 57 10 10	
Fax (0 77 44) 57 20 10	
Internet http://www.sto.de	
e-mail infoservice@sto.eu.com	